

RECEIVED
CENTRAL FAX CENTER

SEP 25 2006

Page 2

USSN 10/786,770

September 25, 2006

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) An automated shutter control for a shutter having a plurality of slats each with a pair of opposing end side edges and ~~an intermediate portion having an external surface~~ upper and lower external surfaces therebetween and which are pivoted in unison, the automated shutter control comprising:

a motor;

a slat interface having a body portion and a connector portion depending therefrom, the connector portion having a contour ~~configured to overlies and connect that overlies and connects to at least one of the upper and lower external surfaces~~ a portion of the intermediate portion only of at least one of the slats of the shutter when so connected; and

a moving assembly moved by the motor and connectable to the ~~slat interface body portion~~ so as to move the slat interface between a first and a second position.

2. (Original) An automated shutter control as claimed in claim 1 wherein the moving assembly is connectable to the body portion of the slat interface.

3. (Original) An automated shutter control as claimed in

Page 3

USSN 10/786,770

September 25, 2006

claim 1 wherein the body portion includes an elongate slot and the moving assembly includes an engagement pin, the engagement pin being received within the elongate slot.

4. (Previously amended) An automated shutter control as claimed in claim 1 wherein the moving assembly comprises a screw threaded shaft connected to the motor and rotated about its axis by the motor, and a carriage assembly threadedly mounted on a jack screw so that rotation of the jack screw moves the carriage assembly in a reciprocating linear manner along the jack screw, the direction of movement of the carriage assembly being determined by the direction of rotation of the jack screw.

5. (Original) An automated shutter control as claimed in claim 4 wherein the carriage assembly comprises a carriage body having a threaded passage therein for mounting on the jack screw, and an engagement pin extending from the carriage body, the engagement pin being connectable to the slat interface.

6. (Original) An automated shutter control as claimed in claim 5 wherein the body portion of the slat interface includes an elongate slot in which the engagement pin is received.

7. (Original) An automated shutter control as claimed in

Page 4

USSN 10/786,770

September 25, 2006

claim 1 wherein the connector portion comprises a flat plate portion connectable to a flat surface of the slat, and a curved portion corresponding in shape to a curve on the slat, the flat plate portion and curved portion together at least partially engaging the slat.

8. (Original) An automated shutter control as claimed in claim 7 further comprising a second flat plate portion connected to the curved portion to engage a second surface of the slat.

9. (Original) An automated shutter control as claimed in claim 1 wherein the connector portion comprises a sleeve dimensioned and configured to engage an end of one of the slats.

10. (Original) An automated shutter control as claimed in claim 1 further comprising adhesive means on the connector portion, the adhesive means providing adhesion to a slat when the slat interface is connected to a slat.

11. (Original) An automated shutter control as claimed in claim 10 wherein the adhesive means comprises a double-sided tape.

12. (Original) An automated shutter control as claimed in claim 10 wherein the adhesive comprises glue.

Page 5

USSN 10/786,770

September 25, 2006

-
13. (Original) An automated shutter control as claimed in claim 1 wherein the body portion of the slat interface comprises a projection extending upwardly from the connector portion, the projection including receiving means for engagement with the moving assembly.
14. (Original) An automated shutter control as claimed in claim 1 further comprising a gear box between the motor and the moving assembly.
15. (Original) An automated shutter control as claimed in claim 1 further comprising a power source for the motor.
16. (Original) An automated shutter control as claimed in claim 15 wherein the power source comprises a solar energy collector and a solar energy storage device.
17. (Original) An automated shutter control as claimed in claim 16, further comprising a housing for the motor and at least a part of the moving assembly, the solar collector being mounted on the outside of the housing for exposure to sunlight.
18. (Original) An automated shutter control as claimed in claim 15 wherein the power source is a battery.

RECEIVED
CENTRAL FAX CENTER

SEP 25 2006

Page 6

USSN 10/786,770

September 25, 2006

19. (Original) An automated shutter control as claimed in claim 15 wherein the power source is an AC supply outlet.

20. (Original) An automated shutter control as claimed in claim 1 further comprising a remote activation system for activating the motor from a distance.

21. (Original) An automated shutter control as claimed in claim 20 wherein the remote activation system comprises a signal-receiver associated with the automated shutter control, a switch member for activating the motor in response to a signal received from the receiver, and a remote transmitter for transmitting a signal to the signal receiver to activate the motor.

22. (Original) An automated shutter control as claimed in claim 21 wherein the remote transmitter has at least two input buttons to effect movement of the slat interface to either the first or the second position respectively.

23. (Original) An automated shutter control as claimed in claim 1 wherein the connector portion incorporates a hole, and a screw which passes through the hole to fasten the connector portion to a slat.

Page 7

USSN 10/786,770

September 25, 2006

24. (Original) An automated shutter control as claimed in claim 1 wherein the body portion includes an aperture and the moving assembly includes a clevis joint, the clevis joint being received by the aperture.

25. (Original) An automated shutter control as claimed in claim 1 wherein the body portion includes a ball and the moving assembly includes a socket, the socket being received by the ball.

26. (Original) An automated shutter control as claimed in claim 1 further comprising a slip mechanism to prevent further movement of the shutters when an obstruction is present.

27. (Currently amended) A shutter and automated shutter control combination comprising:

a shutter having a plurality of parallel slats each with a pair of opposing end side edges and upper and lower external surfaces ~~an intermediate portion having an external surface~~ therebetween and which are pivoted in unison;

an automated shutter control adjacent the plurality of slats, the automated shutter control comprising a housing, a motor within the housing, a slat interface having a body portion and a connector portion depending therefrom, the connector portion having a contour ~~configured to overlie and connect~~ that overlies and connects to at

Page 8

USSN 10/786,770

September 25, 2006

~~least one of the upper and lower external surfaces a portion of the intermediate portion~~ only of at least one of the slats of the shutter when so connected, and a moving assembly partially in the housing and partially extending outside of the housing to releasably connect to the body portion ~~slat interface~~ so as to move the slat interface between a first and a second position.

28. (Original) A shutter and automated shutter control combination as claimed in claim 27 wherein the automated shutter control comprises at least two slat interfaces, each of which is connected to a different slat on the shutter, at least two slat interfaces being moved in unison by the moving assembly.

29. (Currently amended) An automated shutter control for a shutter having a plurality of slats each with a pair of opposing end side edges and upper and lower external surfaces ~~an intermediate portion having an external surface~~ therebetween and which are pivoted in unison, the automated shutter control comprising:

a motor;

a slat interface dimensioned to register with and engage at least a portion of one of the upper and lower external surfaces ~~the intermediate portion~~ only of at least one of the slats of the shutter when so engaged; and

Page 9

USSN 10/786,770

September 25, 2006

a moving assembly, moved by the motor and connectable to the slat interface so as to move the slat interface between a first and a second position.

30. (Currently amended) A method for opening and closing a shutter having a plurality of slats each with an upper and lower external surface ~~comprising between~~ a pair of opposing end side edges ~~and an intermediate portion therebetween~~, the method comprising:

attaching a slat interface contoured to register with and engage at least one of the upper and lower external surfaces a ~~portion of the intermediate portion~~ only of at least one of the slats of the shutter when so engaged;

locating a moving assembly adjacent the slat interface so as to engage therewith, the moving assembly not being directly connected to the slats; and

reciprocating the moving assembly so that the slat interface moves between a first and a second position corresponding to the open and closed position of the shutter.

31. (Previously amended) A method as claimed in claim 30 further comprising attaching a solar collector to a shutter control, and locating a power source within the shutter control which is charged by energy derived from the solar panels.

RECEIVED
CENTRAL FAX CENTER

SEP 25 2006

Page 10

USSN 10/786,770

September 25, 2006

32. (Original) A method as claimed in claim 30 further comprising the step of locating a remote activation system on the automated shutter control so that a remote transmitted signal is received by a signal receiver on the automated shutter control, the signal receiver activating the motor to move the slat interface between the first and the second position.

CONTINUED NEXT PAGE